# RADIOACTIVE MATERIALS (FISSILE/LOW TO HIGH LEVEL RADIATION)

## **POTENTIAL HAZARDS**

### HEALTH

- Radiation presents minimal risk to transport workers, emergency response personnel and the public during transportation accidents. Packaging durability increases as potential radiation and criticality hazards of the content increase.
- Undamaged packages are safe. Contents of damaged packages may cause higher external radiation
  exposure, or both external and internal radiation exposure if contents are released.
- Type AF or IF packages, identified by package markings, do not contain life-threatening amounts of
  material. External radiation levels are low and packages are designed, evaluated and tested to control
  releases and to prevent a fission chain reaction under severe transport conditions.
- Type B(U)F, B(M)F and CF packages (identified by markings on packages or shipping papers) contain
  potentially life endangering amounts. Because of design, evaluation and testing of packages, fission
  chain reactions are prevented and releases are not expected to be life endangering for all accidents
  except those of utmost severity.
- The rarely occurring "Special Arrangement" shipments may be of Type AF, BF or CF packages. Package type will be marked on packages, and shipment details will be on shipping papers.
- The transport index (TI) shown on labels or a shipping paper might not indicate the radiation level at one
  meter from a single, isolated, undamaged package; instead, it might relate to controls needed during
  transport because of the fissile properties of the materials. Alternatively, the fissile nature of the contents
  may be indicated by a criticality safety index (CSI) on a special FISSILE label or on the shipping paper.
- Some radioactive materials cannot be detected by commonly available instruments.
- · Water from cargo fire control is not expected to cause pollution.

### FIRE OR EXPLOSION

- These materials are seldom flammable. Packages are designed to withstand fires without damage to contents.
- Radioactivity does not change flammability or other properties of materials.
- Type AF, IF, B(U)F, B(M)F and CF packages are designed and evaluated to withstand total engulfment in flames at temperatures of 800°C (1475°F) for a period of 30 minutes.

### PUBLIC SAFETY

- CALL EMERGENCY RESPONSE Telephone Number on Shipping Paper first. If Shipping Paper not
  available or no answer, refer to appropriate telephone number listed on the inside back cover
- Priorities for rescue, life-saving, first aid, fire control and other hazards are higher than the
  priority for measuring radiation levels.
- Radiation Authority must be notified of accident conditions. Radiation Authority is usually responsible for decisions about radiological consequences and closure of emergencies.
- As an immediate precautionary measure, isolate spill or leak area for at least 25 meters (75 feet) in all directions.
   Stay upwind.
   Keep unauthorized personnel away.
- Detain or isolate uninjured persons or equipment suspected to be contaminated; delay decontamination and cleanup until instructions are received from Radiation Authority.

### PROTECTIVE CLOTHING

 Positive pressure self-contained breathing apparatus (SCBA) and structural firefighters' protective clothing will provide adequate protection against internal radiation exposure, but not external radiation exposure.

### EVACUATION

### Large Spill

Consider initial downwind evacuation for at least 100 meters (330 feet).

#### Fire

 When a large quantity of this material is involved in a major fire, consider an initial evacuation distance of 300 meters (1000 feet) in all directions.

# GUIDE 165

### **EMERGENCY RESPONSE**

### FIRE

- Presence of radioactive material will not influence the fire control processes and should not influence selection of techniques.
- · Move containers from fire area if you can do it without risk.
- Do not move damaged packages; move undamaged packages out of fire zone.

### Small Fire

• Dry chemical, CO<sub>2</sub>, water spray or regular foam.

### Large Fire

Water spray, fog (flooding amounts).

### SPILL OR LEAK

- Do not touch damaged packages or spilled material.
- Damp surfaces on undamaged or slightly damaged packages are seldom an indication of packaging failure. Most packaging for liquid content have inner containers and/or inner absorbent materials.

### Liquid Spill

Package contents are seldom liquid. If any radioactive contamination resulting from a liquid release is
present, it probably will be low-level.

### FIRST AID

- Call 911 or emergency medical service.
- Medical problems take priority over radiological concerns.
- Use first aid treatment according to the nature of the injury.
- · Do not delay care and transport of a seriously injured person.
- · Give artificial respiration if victim is not breathing.
- · Administer oxygen if breathing is difficult.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- Injured persons contaminated by contact with released material are not a serious hazard to health care personnel, equipment or facilities.
- Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.